

SMC KQG2 Range – Metal One Touch (Stainless Steel)

Fluid	Air / Nitrogen / Water / Beverages / Food / Steam
Food Safe	Yes
Operating Pressure Range	-100 kPa to 1 MPa -14.5 Psi to 145 Psi
Temperature Range	-5 to 150 °C (No freezing)
Tube Material	LDPE, Nylon, TPU, PFA
Size Range	4, 6, 8, 10, 12 and 16mm OD



Male connector	Product Code	Tube OD	Thread	Qty Per Pack
	FG-KQG2H06-02S	6.0	1/4" BSP	10
	FG-KQG2H08-02S	8.0	1/4" BSP	10
	FG-KQG2H10-02S	10.0	1/4" BSP	10
	FG-KQG2H12-03S	12.0	3/8" BSP	10

Union Elbow	Product Code	Tube OD (All)	Qty Per Pack
	FG-KQG2L06-00	6.0	10
	FG-KQG2L08-00	8.0	10
	FG-KQG2L10-00	10.0	10
	FG-KQG2L12-00	12.0	10

Union Tee	Product Code	Tube OD (All)	Qty Per Pack
	FG-KQG2T06-00	6.0	10
	FG-KQG2T08-00	8.0	10
	FG-KQG2T10-00	10.0	10
	FG-KQG2T12-00	12.0	10

Male Elbow	Product Code	Tube OD	Thread	Qty Per Pack
	FG-KQG2L06-02S	6.0	1/4" BSP	10
	FG-KQG2L08-02S	8.0	1/4" BSP	10
	FG-KQG2L10-02S	10.0	1/4" BSP	10
	FG-KQG2L12-03S	12.0	3/8" BSP	10