




SMC LQ1 Range – Chemical Resistant (Fluoropolymer)


Fluid	Air / Nitrogen / Water / Chemicals (inc Caustic)
Operating Pressure Range	-100 kpa to 1 MPa
	-14.5 Psi to 145 Psi
Temperature Range	-5 to 150 °C (Air) (No freezing)
Tube Material	PFA, PTFE (Teflon), PVDF (Kynar)
Size Range	4, 6, 8, 10, 12 and 16mm OD



Male connector	Product Code	Tube OD	Tube ID	Thread	Qty Per Pack
	FG-LQ1H21-M	6.0	4.0	1/4" BSP	10
	FG-LQ1H32-M	8.0	6.0	1/4" BSP	10
	FG-LQ1H31-M	10.0	8.0	1/4" BSP	10

Union Elbow	Product Code	Tube OD (All)	Tube ID		Qty Per Pack
	FG-LQ1E21	6.0	4.0		10
	FG-LQ1E32	8.0	6.0		10

Union Tee	Product Code	Tube OD (All)	Tube ID		Qty Per Pack
	FG-LQ1T21	6.0	4.0		10
	FG-LQ1T32	8.0	6.0		10

Male Elbow	Product Code	Tube OD	Tube ID	Thread	Qty Per Pack
	FG-LQ1L31-M	10.0	8.0	1/4" BSP	10